

**Product Name: L-6114**  
**Chemical group: Epoxy acrylic****Description**

L-6114 is an epoxy acrylate with fast curing speed, good surface drying, high gloss, high reactivity, good chemical resistance and good wettability.

**Chemical & physical data**

Appearance	Colorless or yellowish transparent liquid
Viscosity (25°C, CPS)	3000-50000CPS
Chroma (Gardner)	≤3
UV Component (solid content %)	100%
Density (g/cm <sup>3</sup> ,25°C)	1.1±0.1
Acid value (mgkoH/g)	≤2
Functional group number	2

**Performance**

High gloss and high reactivity  
Continuous painting  
Fast curing speed and good surface drying  
Good chemical resistance and wettability

**Application**

UV wood top coating , UV vacuum plating primer, UV paper varnish, UV plastic coating, UV hardware paint, UV nail polish, etc.

**Storage, shelf time and Packing**

This product will be functional for 6 months as long as storing under normal temperature and keeping away from heat and light.

This Product will be packed into 20kg、25kg、200kgs/drum.

The information contained in this TDS is intended as advice only and whilst the information is provided in utmost good faith and has been based on our best information currently available, is to be relied upon at the user's own risk. No representations or warranties are made with regards to its completeness or accuracy and no liability will be accepted by San Qi Chemical for damages of any nature whatsoever resulting from the use of or reliance on the information.