

Product Name: L-8404**Chemical group: Modified Polyurethane acrylic****Description**

L-8404 is a specially modified polyurethane acrylic UV resin. It has good flexibility, good adhesion, fast reaction and other characteristics. It has strong adhesion after UV curing. It is recommended to use various UV laminates and UV adhesives.

Chemical & physical data

Appearance	Transparent liquid
Viscosity (25°C, CPS)	8000-25000CPS
UV Component (solid content %)	100%
Density (g/cm ³ , 25°C)	1.1±0.1
Acid value (mgkoH/g)	2-5
Functional group number	3

Performance

Low shrinkage and good flexibility
Good adhesion to soft and hard plastic and metal
Good wettability of pigments
Strong stickiness after curing

Application

Low shrinkage and good flexibility.
Good adhesion to PP, PET, PVC, paper, BOPP, metal, etc.

Storage, shelf time and Packing

This product will be functional for 1 year as long as storing under normal temperature and keeping away from heat and light.

This Product will be packed into 200kgs/drum.

The information contained in this TDS is intended as advice only and whilst the information is provided in utmost good faith and has been based on our best information currently available, is to be relied upon at the user's own risk. No representations or warranties are made with regards to its completeness or accuracy and no liability will be accepted by San Qi Chemical for damages of any nature whatsoever resulting from the use of or reliance on the information.