

Lencolo 5016W Water-based Anti-scratch Wax Slurry

Description

Lencolo 5016W It is a kind of water-based dispersion of special polymer wax particles, which is easy to use and can be used after simple dispersion and mixing. Can provide excellent scratch resistance, abrasion resistance, smooth feel and matting efficiency.

Technical data

Component	Aqueous dispersion of special polymer wax
Appearance	Slightly white liquid
Active ingredient	35±1%
Solvents	Water
Density	0.90±0.03g/cm ³

Performance

Can significantly improve the wear resistance and scratch resistance of various water-based coatings

Delicate hand feeling, good transparency, can provide a soft and silky touch

Applications

Various water-based industrial paints, water-based wood paints, water-based UV paints, water-based floor paint systems, etc.

Usage

Store at 0-35°C, avoid direct sunlight or high temperature places

Shake well before use and use up as soon as possible after opening

Avoid use in high temperature and extremely low temperature environments

Addition amount: 2~10%

According to the requirements, it is suggested that the user should conduct experiments to determine the optimal dosage before use.

Storage

To prevent the product from polymerization and gelling, please keep it sealed and away from heat and light. Recommended storage temperature is not higher than 30°C. Unused products must be sealed and stored in a timely manner and cannot be stored in the open. Safe storage time is 6 months at room temperature(25°C) and under ventilation. 25KG/barrel

Tips:Lencolo 5016W water-based universal wax paste, cost-effective, does not affect transparency and gloss.

Note: Technical data represents typical values only. In view of the differences in formulas, production process, conditions, all the above statements must be adjusted according to the actual situation, our company does not make any promises. Our company reserves the right to reform its products without prior notice of any changes.