

Lencolo 5002A Recoatable Soft Touch Additive

Description

Lencolo 5002A is a special silicone modified polymer, which can improve the soft touch, smoothness and scratch resistance of the paint film. It is a touch agent that can be screen printed and recoated.

Technical data

Component	Special modified silicone polymers
Appearance	Slightly yellow liquid
Specific gravity	1.05
Active ingredient (%)	100%

Performance

After adding, it provides soft touch feel without affecting recoating, and can be silk-screened on the surface of the coating film.

It can give the elastic paint film an excellent feel effect, and has good compatibility with most resins. It can not only increase the feel of the elastic paint, but also reduce the surface tension, improve the wetting performance of the paint substrate, and promote the fluidity of the paint film.

Applications

Elastic paint, rubber paint

Usage

For the full amount 1 - 4%

It is recommended that the user determine the optimum dosage through experiments before use.

Storage

To prevent the product from polymerization and gelling, please keep it sealed and away from heat and light. Recommended storage temperature is not higher than 30°C. Unused products must be sealed and stored in a timely manner and cannot be stored in the open. Safe storage time is 6 months at room temperature(25°C) and under ventilation. 25KG/barrel

Tips:The highlight of Lencolo 5002A is recoatable and able to apply silkscreen printing.

Note: Technical data represents typical values only. In view of the differences in formulas, production process, conditions, all the above statements must be adjusted according to the actual situation, our company does not make any promises. Our company reserves the right to reform its products without prior notice of any changes.