

Lencolo 5002 Delicate Slippery Soft Touch Additive

Description

Lencolo 5002 is a special organosilicon modified polymer with excellent elasticity and fine soft touch performance, and the paint film is not white, smooth and dry, has the effect of increasing surface smoothness and increasing gloss.

Technical data

Component	Special modified silicone polymers
Appearance	Transparent liquid
Specific gravity	1.05
Active ingredient (%)	100%

Performance

It can give the elastic paint film an excellent soft touch effect, and has good compatibility with most resins. It can not only increase the feel of the elastic paint, but also reduce the surface tension, improve the wetting performance of the paint substrate, and promote the fluidity of the paint film.

Applications

Elastic paint, rubber paint

Usage

For the full amount 1 - 4%

It is recommended that the user determine the optimum dosage through experiments before use.

Storage

To prevent the product from polymerization and gelling, please keep it sealed and away from heat and light. Recommended storage temperature is not higher than 30°C. Unused products must be sealed and stored in a timely manner and cannot be stored in the open. Safe storage time is 6 months at room temperature(25°C) and under ventilation. 25KG/barrel

Tips:Lencolo 5002 has good compatibility, delicate soft touch and leveling effect.

Note: Technical data represents typical values only. In view of the differences in formulas, production process, conditions, all the above statements must be adjusted according to the actual situation, our company does not make any promises. Our company reserves the right to reform its products without prior notice of any changes.