

## Lencolo 4002 Baking Paint Adhesion Promoter

### Description

**Lencolo 4002** is a complex modified polyester compound that promotes adhesion of coatings to non-ferrous metal surfaces.

### Technical data

Component	Compound Modified Polyester Compound
Appearance	Transparent liquid
Specific gravity	1.05
Active ingredient	80%
Solvent	Isopropanol
Acid values	60~80mgKOH/g

### Performance

Promotes the adhesion of coatings to difficult non-ferrous metal surfaces.

It can improve the ductility and impact resistance of the coating film.

Rapid baking at high temperature does not change color, and does not affect the weather resistance of the coating film.

Does not affect the storage stability of the paint.

### Applications

Alkyd, acrylic and other baking coatings.

### Usage

Adding amount: 1.5%-2.5% for the full amount

Users are recommended to determine the best addition amount by experiment before use.

### Storage

To prevent the product from polymerization and gelling, please keep it sealed and away from heat and light. Recommended storage temperature is not higher than 30°C. Unused products must be sealed and stored in a timely manner and cannot be stored in the open. Safe storage time is 6 months at room temperature( 25°C) and under ventilation. 25KG/barrel

**Tips:Lencolo 4002 is designed to improve adhesion to non-ferrous metals in a variety of baking systems.**

Note: Technical data represents typical values only. In view of the differences in formulas, production process, conditions, all the above statements must be adjusted according to the actual situation, our company does not make any promises. Our company reserves the right to reform its products without prior notice of any changes.