

## Lencolo 3108 Large Area Recoatable Leveling Agent

### Description

**Lencolo 3108** Is a polyacrylate copolymer solution, can improve leveling and gloss, and can prevent shrinkage, does not affect recoating and intercoat adhesion, only slightly reduced surface tension, has thermal stability.

### Technical data

Component	Polyacrylate copolymer solution
Appearance	Transparent liquid
Specific gravity	0.92
Active ingredient	52%
Solvent	Alkylbenzene

### Performance

It is suitable for high-grade paints and varnishes of various industrial coatings, improving leveling and gloss, and preventing shrinkage craters. Excellent miscibility to most base materials, no turbidity to varnishes,

Does not cause haze on colored paints. Especially suitable for spray coatings with large area products agent.

### Applications

Automotive refinish varnish, wood coating, plastic coating, coil steel coating, anti-corrosion coating and other solvent-based coatings, UV coatings.

### Usage

Addition amount: 0.1%~1.0% of the total amount

It is recommended that users determine the optimal dosage through experiments before use.

### Storage

To prevent the product from polymerization and gelling, please keep it sealed and away from heat and light. Recommended storage temperature is not higher than 30°C. Unused products must be sealed and stored in a timely manner and cannot be stored in the open. Safe storage time is 6 months at room temperature( 25°C) and under ventilation. 25KG/barrel

**Tips:Lencolo 3108 is suitable for large area leveling when used in topcoat, and does not affect recoatability when used in primer for leveling.**

Note: Technical data represents typical values only. In view of the differences in formulas, production process, conditions, all the above statements must be adjusted according to the actual situation, our company does not make any promises. Our company reserves the right to reform its products without prior notice of any changes.