

Lencolo 3002 Fast Leveling Agent

Description

Lencolo 3002 has good compatibility with various resins, suitable for water-based, solvent-based, solvent-free, UV coatings, with excellent leveling, substrate wetting, anti-cratering properties, good recoatability.

Technical data

Component	Modified organosiloxane polymer
Appearance	Transparent liquid
Specific gravity	1.4±0.05
Active ingredient	100%

Performance

Excellent substrate wetting, anti-cratering property
Excellent compatibility, recoatability
Excellent versatility for waterborne, solventborne and UV-curable systems
Provides excellent leveling and slippery properties to the coating film
Good dispersion and arrangement of matte powder, smooth coating film can be obtained
Fast leveling

Applications

Water-based coatings, solvent-based industrial coatings, UV coatings, etc.

Usage

It can be added at any stage in the production process, generally 0.05% -0.4% by weight of the coating.

It is recommended that users determine the optimal dosage through experiments before use

Storage

To prevent the product from polymerization and gelling, please keep it sealed and away from heat and light. Recommended storage temperature is not higher than 30°C. Unused products must be sealed and stored in a timely manner and cannot be stored in the open. Safe storage time is 6 months at room temperature(25°C) and under ventilation. 25KG/barrel

Tips: Lencolo 3002 is fast leveling, recoatable and especially suitable for matte systems.

Note: Technical data represents typical values only. In view of the differences in formulas, production process, conditions, all the above statements must be adjusted according to the actual situation, our company does not make any promises. Our company reserves the right to reform its products without prior notice of any changes.