

Lencolo 2192 Special Defoamer for Wood Paint

Description

Lencolo 2192 is a non-silicon defoamer, especially suitable for light-curing coatings system, has extremely excellent compatibility, and has strong defoaming and defoaming capabilities, does not affect recoatability, does not cause adverse interactions with light-curing systems, No curtain breakage during curtain coating application.

Technical data

| | |
|-------------------|---------------------------|
| Component | Non-silicon polymer |
| Appearance | Light yellow clear liquid |
| Specific gravity | 1.05 |
| Active ingredient | 100% |

Performance

Especially suitable for light-curing coating systems;
Extremely excellent compatibility, and has strong defoaming and defoaming ability at the same time, without affecting recoatability.
Good compatibility with various resins and can be used in UV, PU varnishes etc.

Applications

Light-curing coatings, solvent-free coatings, UV roller coating, curtain coating, spray coating, etc.

Usage

Addition amount: 0.3~1.0% of the total amount

Users are advised to conduct experiments to determine the optimal dosage before use.

Storage

To prevent the product from polymerization and gelling, please keep it sealed and away from heat and light. Recommended storage temperature is not higher than 30°C. Unused products must be sealed and stored in a timely manner and cannot be stored in the open. Safe storage time is 6 months at room temperature(25°C) and under ventilation. 25KG/barrel

Tips: Lencolo 2192 contains 100% solids, has strong defoaming ability, good compatibility, especially suitable for solvent-free UV systems.

Note: Technical data represents typical values only. In view of the differences in formulas, production process, conditions, all the above statements must be adjusted according to the actual situation, our company does not make any promises. Our company reserves the right to reform its products without prior notice of any changes.