

Lencolo 3007 Anti-graffiti Additive

Description

Lencolo 3007 is with hydroxyl, can react with resin, is high effective anti-graffiti additive suitable for any system.

Technical data

Component	Silicone modified polyacrylate polymer
Appearance	Transparent liquid
Specific gravity	0.99
Active ingredient	100%

Performance

Promote leveling of the coating film, have a strong anti-fouling effect, make the coating film easy to clean, and can be used as an anti-graffiti additives, compatible with most solvent systems, used in solvent-based and UV light curing system.

Applications

Industrial coatings, UV coatings

Usage

Generally, the coating weight ratio is 2%-6%, and it should be added in the final stage of the production process, with higher shear force.

It is suggested that users conduct experiments to determine the optimal dosage before use.

Storage

To prevent the product from polymerization and gelling, please keep it sealed and away from heat and light. Recommended storage temperature is not higher than 30°C. Unused products must be sealed and stored in a timely manner and cannot be stored in the open. Safe storage time is 6 months at room temperature(25°C) and under ventilation. 25KG/barrel

Tips: Lencolo 3007 is the one with the best compatibility among anti-fouling additives, and its anti-fouling performance is average.

Note: Technical data represents typical values only. In view of the differences in formulas, production process, conditions, all the above statements must be adjusted according to the actual situation, our company does not make any promises. Our company reserves the right to reform its products without prior notice of any changes.