

---

**Lencolo 4010 High Performance UV Surface Treatment Agent****Description**

**Lencolo 4010** is a special polysiloxane polymer, which is an environmentally friendly and energy-saving surface treatment agent. It can be used as UV rework agent, with strong applicability to UV coatings with good adhesion.

**Technical data**

Component	Special polysiloxane polymer
Appearance	Slightly yellow liquid
Active ingredient	25%
Acid value (mg KOH/g)	20
Solvent	Benzene,esters

**Performance**

It has excellent adhesion to the UV layer and can be used as UV rework water. It has strong applicability to various UVs and good adhesion.

It can improve the adhesion on difficult-to-adhesive surfaces such as glass, ceramics, stone, acrylic, PP, and aluminum-magnesium alloys.

Suitable for metal processing.

**Usage**

Use Lencolo 4010: toluene: ethyl ester = 1: 2.5: 2.5 to dilute, (use directly after diluting 1:5)

When used as UV rework agent, after spraying on the UV surface, it can spray UV coating again at 65°C for 5-10 minutes.

**Storage**

To prevent the product from polymerization and gelling, please keep it sealed and away from heat and light. Recommended storage temperature is not higher than 30°C. Unused products must be sealed and stored in a timely manner and cannot be stored in the open. Safe storage time is 6 months at room temperature( 25°C) and under ventilation. 25KG/barrel

**Tips: Lencolo 4010 has strong applicability to various UV applications, good adhesion during rework, and contains halogen**

Note: Technical data represents typical values only. In view of the differences in formulas, production process, conditions, all the above statements must be adjusted according to the actual situation, our company does not make any promises. Our company reserves the right to reform its products without prior notice of any changes.