

L-6905B Anti-graffiti UV Resin

Description

L-6905B It is fluorocarbon modified UV polyurethane resin with high leveling, high fullness, good anti-graffiti and anti-fingerprint effects.

Technical data

Appearance	Colorless transparent liquid
Viscosity (25°C, CPS)	15,000 - 25,000
Density (g/cm ³ , 25°C)	1.1±0.1
UV component (%)	98
Acid value (mg KOH/g)	1
Refractive index	1.487
Shore hardness	87D
Functional group	6

Performance

High leveling, high fullness, high transparency

Anti-graffiti, anti-fingerprint

Water drop contact angle is over 105 degrees.

Applications

Mobile phone anti-graffiti UV coating, plastic anti-graffiti UV coating, functional film hardening fluid, anti-graffiti UV coating, car lamp refinish paints, etc.

Storage

To prevent the product from polymerization and gelling, please keep it sealed and away from heat and light. Safe storage time is 6 months at room temperature(25°C) and under ventilation.

This product will be packed into 20KG/25KG/200KG/barrel

Tips: L-6905B has good fullness, very good transparency, anti-graffiti effect, water drop contact angle over 105 degrees.

Note: Technical data represents typical values only. In view of the differences in formulas, production process, conditions, all the above statements must be adjusted according to the actual situation, our company does not make any promises. Our company reserves the right to reform its products without prior notice of any changes.