

## L-6905A Anti-graffiti UV Resin

### Description

**L-6905A** Anti-graffiti UV resin, fluorocarbon modified high-reactive resin, with good leveling, good fullness, high hardness, anti-graffiti, anti-fingerprint effect, the fluorine content does not exceed the standard, recommended for PVC floor, wood floor, furniture coating and other anti-fouling/anti-stain coatings.

### Technical data

Appearance	Colorless transparent liquid
Viscosity (25°C, CPS)	13,000 - 23,000
Density (g/cm <sup>3</sup> , 25°C)	≥99
UV component (%)	1.1±0.1
Acid value (mg KOH/g)	1
Refractive index	1.473
Shore hardness	88D
Functional group	6

### Performance

Good leveling, high fullness  
Anti-graffiti, anti-fingerprint  
Scratch and abrasion resistant

### Applications

It is recommended for anti-stain and wear-resistant coatings for PVC floors, wood floors, and furniture paints.

### Storage

To prevent the product from polymerization and gelling, please keep it sealed and away from heat and light. Safe storage time is 6 months at room temperature( 25°C) and under ventilation.  
This product will be packed into 20KG/25KG/200KG/barrel

**Tips: L-6905A has good anti-stain effect among anti-graffiti UV resins and is cost-effective.**

Note: Technical data represents typical values only. In view of the differences in formulas, production process, conditions, all the above statements must be adjusted according to the actual situation, our company does not make any promises. Our company reserves the right to reform its products without prior notice of any changes.