

L-6905A Cost-Effective Anti-Graffiti UV-Curable Resin

Description

L-6905A Anti-graffiti UV resin, fluorocarbon modified high-reactive resin, with good leveling, good fullness, high hardness, anti-graffiti, anti-fingerprint effect, the fluorine content does not exceed the standard, recommended for PVC floor, wood floor, furniture coating and other anti-fouling/anti-stain coatings.

Technical data

Appearance	Slightly hazy liquid
Viscosity (25°C, CPS)	13,000 - 23,000
UV Content (%)	≥99
Density (g/cm ³ , 25°C)	1.1±0.1
Acid value (mg KOH/g)	1
Refractive index	1.473
Shore hardness	88D
Functional group	6

Product Features

Good leveling, high fullness
Anti-graffiti, anti-fingerprint
Scratch and abrasion resistant

Applications

It is recommended for anti-stain and wear-resistant coatings for PVC floors, wood floors, and furniture paints.

Storage Conditions

To prevent the product from polymerization and gelling, please keep it sealed and away from heat and light. Safe storage time is 6 months at room temperature(25°C) and under ventilation.
This product will be packed into 20KG/25KG/200KG/barrel

Tips: L-6905A has good anti-stain effect among anti-graffiti UV resins and is cost-effective.

Note: Technical data represents typical values only. In view of the differences in formulas, production process, conditions, all the above statements must be adjusted according to the actual situation, our company does not make any promises. Our company reserves the right to reform its products without prior notice of any changes.