

## **Lencolo 3002 Fast Leveling Agent**

### **Description**

**Lencolo 3002** compatible with various resins and suitable for water-based, solvent-based, solvent-free, and UV coatings; offers excellent leveling, substrate wetting, anti-shrinkage properties, and good recoatability.

### **Technical Data**

Component	Modified organosiloxane polymer
Appearance	Transparent liquid
Specific gravity	1.4±0.05
Active ingredient	100%

### **Product Features**

Excellent substrate wetting, anti-cratering property  
Outstanding compatibility and recoating performance  
Highly versatile, suitable for waterborne, solvent-based, and UV-curable systems  
Provides superior leveling and smooth touch to the film  
Promotes good dispersion and orientation of matte powders, resulting in smooth coatings  
Fast leveling speed

### **Applications**

Water-based coatings; solvent-based industrial coatings; UV coatings, etc.

### **Recommended Usage**

It can be added at any stage of the production process, typically at 0.05–0.4% by weight of the coating.

Users are advised to determine the optimal dosage through trials prior to use.

### **Storage Conditions**

To prevent premature polymerization due to the high reactivity of this product, keep it tightly sealed and store away from heat sources and direct sunlight. It is recommended to maintain storage temperature below 30 °C. Unused product should be promptly resealed and must not be left open. Under ventilated conditions at 25 °C, the product has a safe storage period of 6 months. Available

**Tips: Lencolo 3002 is fast leveling, recoatable and especially suitable for matte systems.**

Note: Technical data represents typical values only. In view of the differences in formulas, production process, conditions, all the above statements must be adjusted according to the actual situation, our company does not make any promises. Our company reserves the right to reform its products without prior notice of any changes.