

Lencolo 3007 Anti-graffiti Additive

Description

Lencolo 3007 is a hydroxy-functional additive that can react with resins, suitable as a high-performance anti-graffiti agent for any coating system.

Technical Data

Composition	Organosilicon-modified acrylate polymer
Appearance	Transparent liquid
Specific Gravity	0.99
Active Content	100%

Product Features

Promote leveling of the coating film, have a strong anti-fouling effect, make the coating film easy to clean, and can be used as an anti-graffiti additives, compatible with most solvent systems, used in solvent-based and UV light curing system.

Applications

Industrial coatings; UV coatings

Recommended Usage

Generally added at 2–6% by weight of the coating, preferably in the final stage of production under relatively high shear.

Users are advised to determine the optimal dosage through trials prior to use.

Storage Conditions

To prevent premature polymerization due to the high reactivity of this product, keep it tightly sealed and store away from heat sources and direct sunlight. It is recommended to maintain storage temperature below 30 °C. Unused product should be promptly resealed and must not be left open. Under ventilated conditions at 25 °C, the product has a safe storage period of 6 months. Available packaging: 25 kg per drums

Tips: Lencolo 3007 is the most compatible among anti-fouling additives, with moderate anti-fouling performance.

Note: Technical data represents typical values only. In view of the differences in formulas, production process, conditions, all the above statements must be adjusted according to the actual situation, our company does not make any promises. Our company reserves the right to reform its products without prior notice of any changes.