

## Lencolo 3110 Leveling Agent for Baked Coatings

### Description

**Lencolo 3110** is a polyester-modified polydimethylsiloxane solution that reduces the surface tension of coating systems, improves substrate wetting, prevents pinholes, enhances surface slip and gloss, and improves leveling.

### Technical Data

Composition	Polyester modified polydimethylsiloxane
Appearance	Transparent liquid
Specific Gravity	1.04
Active Content (%)	97%

### Product Features

It is a heat-resistant silicone-based additive that does not thermally decompose between 150–230 °C. When recoating in baked systems, it does not cause loss of adhesion or surface defects. It strongly enhances surface slip and substrate wetting. Especially recommended as a preferred leveling additive in baked coatings, it also provides anti-pinhole functionality.

### Applications

Baked paint coatings, coil coatings, especially suitable for baked paint systems.

### Recommended Usage

**Dsage:** 0.05% ~ 0.3% of total formulation

Users are advised to determine the optimal dosage through trials prior to use.

### Storage Conditions

To prevent premature polymerization due to the high reactivity of this product, keep it tightly sealed and store away from heat sources and direct sunlight. It is recommended to maintain storage temperature below 30 °C. Unused product should be promptly resealed and must not be left open. Under ventilated conditions at 25 °C, the product has a safe storage period of 6 months. Available packaging: 25 kg per drum

### Tips: Lencolo 3110 is the best leveling additive for baking paint systems.

Note: Technical data represents typical values only. In view of the differences in formulas, production process, conditions, all the above statements must be adjusted according to the actual situation, our company does not make any promises. Our company reserves the right to reform its products without prior notice of any changes.