

Lencolo 5001 Skin Feel Soft Touch Additive

Description

Lencolo 5001 is a special organosilicon modified polymer with excellent elasticity and hand resistance, which improves the fleshy and soft touch of the paint film without whitening.

Technical Data

| | |
|--------------------|--|
| Composition | Special organosilicon-modified polymer |
| Appearance | Transparent liquid |
| Specific Gravity | 1.05 |
| Active Content (%) | 100% |

Product Features

It can endow the elastic paint film with excellent soft touch effect, and has good compatibility with most resins. It is not only enhancing the feel of elastic paints but also improving leveling and scratch resistance, and assisting in the orientation of matting powders.

Applications

Elastic coatings, rubber paints

Recommended Usage

Dosage: 1 - 4% based on total formulation weight.

Users are advised to determine the optimal dosage through trials prior to use.

Storage Conditions

To prevent premature polymerization due to the high reactivity of this product, keep it tightly sealed and store away from heat sources and direct sunlight. It is recommended to maintain storage temperature below 30 °C. Unused product should be promptly resealed and must not be left open. Under ventilated conditions at 25 °C, the product has a safe storage period of 6 months. Available packaging: 25 kg per drum

Tips: Lencolo 5001 is the first choice product for thick texture skin feel soft touch additive.

Note: Technical data represents typical values only. In view of the differences in formulas, production process, conditions, all the above statements must be adjusted according to the actual situation, our company does not make any promises. Our company reserves the right to reform its products without prior notice of any changes.