

Lencolo 5002 Delicate Slippery Soft Touch Additive

Description

Lencolo 5002 is a special organosilicon modified polymer with excellent elasticity and delicate soft touch performance. It does not cause whitening of the coating. Provides smooth, dry surface feel, enhances surface slip, and increases gloss.

Technical Data

Composition	Special organosilicon-modified polymer
Appearance	Transparent liquid
Specific Gravity	1.05
Active Content (%)	100%

Product Features

It can give the elastic paint film an excellent soft touch effect, and has good compatibility with most resins. In addition to enhancing the feel of elastic coatings, it reduces surface tension, improves substrate wetting, and promotes coating flow.

Applications

Elastic coatings, rubber paints

Recommended Usage

Dosage: 1 - 4% based on total formulation weight.

Users are advised to determine the optimal dosage through trials prior to use.

Storage Conditions

To prevent premature polymerization due to the high reactivity of this product, keep it tightly sealed and store away from heat sources and direct sunlight. It is recommended to maintain storage temperature below 30 °C. Unused product should be promptly resealed and must not be left open. Under ventilated conditions at 25 °C, the product has a safe storage period of 6 months. Available packaging: 25 kg per drum

Tips:Lencolo 5002 has good compatibility, delicate soft touch and leveling effect.

Note: Technical data represents typical values only. In view of the differences in formulas, production process, conditions, all the above statements must be adjusted according to the actual situation, our company does not make any promises. Our company reserves the right to reform its products without prior notice of any changes.