

Lencolo 5002A Recoatable Soft Touch Additive

Description

Lencolo 5002A is a special silicone modified polymer that enhances the coating's delicate tactile feel, smoothness, and scratch resistance. It is a recoatable and screen-printable tactile agent.

Technical Data

Composition	Special organosilicon-modified polymer
Appearance	Slightly yellow liquid
Specific Gravity	1.05
Active Content (%)	100%

Product Features

When added, it provides an enhanced tactile feel without affecting recoating and allows screen printing on the coating surface.

It imparts excellent tactile properties to elastic coatings, is compatible with most resins, improves substrate wetting by lowering surface tension, and promotes coating flow and leveling.

Applications

Elastic coatings, rubber paints

Recommended Usage

Dosage: 1 - 4% based on total formulation weight.

Users are advised to determine the optimal dosage through trials prior to use.

Storage Conditions

To prevent premature polymerization due to the high reactivity of this product, keep it tightly sealed and store away from heat sources and direct sunlight. It is recommended to maintain storage temperature below 30 °C. Unused product should be promptly resealed and must not be left open. Under ventilated conditions at 25 °C, the product has a safe storage period of 6 months. Available packaging: 25 kg per drum

Tips: The highlight of Lencolo 5002A is recoatable and able to apply silkscreen printing.

Note: Technical data represents typical values only. In view of the differences in formulas, production process, conditions, all the above statements must be adjusted according to the actual situation, our company does not make any promises. Our company reserves the right to reform its products without prior notice of any changes.