

Lencolo 8708 Harden and Wear-resistant Additive

Description

Lencolo 8708 is a special silicone-modified resin that can be used for hardening and temperature-resistant modification of amino baking paint systems and polyester-modified silicones. It can be added at any stage of the original paint production, which can significantly improve the normal temperature hardness and hot hardness of the paint, up to 8H (Mitsubishi Pencil).

Technical data

Component	Special silicone modified resin
Appearance	Transparent liquid
Active ingredients	20±2%
Solvents	Isopropyl alcohol,

Performance

Used as hardening modified resin. It can be used as hardening and temperature-resistant modification for amino baking paint systems and polyester-modified silicones. It can be added at any stage of the original paint production, which can significantly improve the normal temperature hardness and hot hardness of the paint, up to 8H (Mitsubishi Pencil).

Applications

Amino paint system, polyester modified silicone hardening, temperature resistance modification purposes

Substrate: iron, steel, aluminum alloy, aluminum, stainless steel; copper, glass, fiberglass, etc. are generally degreased and sandblasted.

Note: Test the compatibility of the product and the system before use.

Storage

To prevent the product from polymerization and gelling, please keep it sealed and away from heat and light. Recommended storage temperature is not higher than 30°C. Unused products must be sealed and stored in a timely manner and cannot be stored in the open. Safe storage time is 6 months at room temperature(25°C) and under ventilation. 25KG/180KG/drum

Note: Technical data represents typical values only. In view of the differences in formulas, production process, conditions, all the above statements must be adjusted according to the actual situation, our company does not make any promises. Our company reserves the right to reform its products without prior notice of any changes.