

Lencolo 8716 Wrinkle Texture Additive

Description

Lencolo 8716 Added in the final stage of dilution or toning stage, it can show the three-dimensional effect of fine patterns. Applied to aluminum paste alkyd baking paint system and oxidative drying blend paint system, both have fine pattern three-dimensional effect

Technical data

Component	High molecular polysiloxane compound
Appearance	Transparent liquid
Active ingredients	10±2%
Density (g/cm3 , 25°C)	0.95

Performance

It can make the hammer pattern of aluminum powder paint uniform, exquisite, and have a strong three-dimensional effect. And because its molecular chain structure is quite stable, the pattern will not change greatly during storage

Applications

Solvent-based aluminum powder paint system baking paint, mixed paint, spray paint

Note: Test the compatibility of the product and the system before use.

Usage

In the final stage of paint mixing and toning, it is necessary to add a smaller amount for bigger texture, and a larger amount of small texture.

Add to the full amount: 0.05-0.5%

Storage

To prevent the product from polymerization and gelling, please keep it sealed and away from heat and light. Recommended storage temperature is not higher than 30°C. Unused products must be sealed and stored in a timely manner and cannot be stored in the open. Safe storage time is 6 months at room temperature(25°C) and under ventilation. 25KG/200KG/drum

Tips: Lencolo 8716 is mostly used in PU and baking paint systems, and can also be used in water-based systems.

Note: Technical data represents typical values only. In view of the differences in formulas, production process, conditions, all the above statements must be adjusted according to the actual situation, our company does not make any promises. Our company reserves the right to reform its products without prior notice of any changes.